

NEPTUNE-5500



The NEPTUNE-5500 is built tough to meet the demanding requirements of harsh conditions for tough washdown environments and corrosive chemical industries. Large easy-to-read, bright green, one inch tall digits ensure maximize operator visibility and minimize fatigue while maintaining high product throughput. Polished, 304 stainless steel construction provides high durability and a long term attractive sanitary appearance. With simple five key operation, this scale combines simplicity, practicality and high value.

NEPTUNE-5500

STAINLESS STEEL HIGH SPEED CHECKWEIGHER

STANDARD 5500 INDICATOR FEATURES

- ▷ **HIGH SPEED OPERATIONS:**
At thirty updates per second, zero to target and back to zero ensures maximum throughput and productivity
- ▷ **Four units of measure:** pushbutton select to read in pounds, ounces, pound - ounce, kilograms.
- ▷ **Check weigh annunciators:** amber/under, green/accept, red/over
- ▷ **Internal beeper for audible alert**
- ▷ **Adjustable Tilt Display:** Allows adjustable indicator placement for best viewing angle.
- ▷ **Serial RS232C Data Output:** This bi-directional port is selectable for interface to a printer, remote display or computer at 1200-9600 baud.
- ▷ **Complete Print Format:** Contains gross weight, OVER or UNDER indication, time, date and ticket number.
- ▷ **Time and Date Memory Standard**
- ▷ **Digital Keyboard Calibration**
- ▷ **3 - 5 Volt TTL Setpoint Outputs**
- ▷ **NTEP: PENDING**

SCALE BASE STANDARD FEATURES

- ▷ **RUGGED HEAVY DUTY STEEL CONSTRUCTION:**
Heavy-duty stainless steel construction with additional understructure channel supports, assures durability and precision in rugged industrial environments.
- ▷ **150% OVERLOAD PROTECTION:**
Five mechanical overload stops incorporated with the heavy-duty double plate design assures superior overload ability.
- ▷ **SEALED ALUMINUM LOAD CELL**
- ▷ **ONE YEAR WARRANTY**
- ▷ **RUGGED 304 STAINLESS STEEL WEIGH PAN:**
All Neptune scales come equipped with a heavy gauge stainless steel weigh pan that is designed for low maintenance.
- ▷ **SIX FEET OF LOAD CELL CABLE**

Specifications

Construction: Type 304 Stainless Steel to NEMA 4X Standard
Power Requirements: 117 VAC - 50/60 Hz at 0.5 Amp
- Optional: Line Power 220 VAC - 50/60 Hz at 0.25 Amp
Display: 6 Digits Plus Sign, 1" High, 7 Segment LED Display
Display Update Rate: 8 Per Second
Selectable Resolution: 500 - 50000 displayed counts
Operating Temperature: -10°C to 40°C (14°F to 104°F)

CAPACITIES	SIZES
10, 25, 50, 100 lb	10" x 10" x 3"
10, 25, 50, 100 lb	12" x 12" x 3"
250, 500, 1000 lb	18" x 18" x 5"
500, 1000 lb	24" x 24" x 5"

Optional Accessories

Stainless Steel Load Cell
21" high column
18" x 18" roller ball top
24" x 24" roller ball top



YOUR AUTHORIZED TRANSCELL DEALER IS:

Specifications and features subject to change without notice.



TRANSCELL TECHNOLOGY, INC.

975 Deerfield Pkwy, Buffalo Grove, IL 60089

Tel (847) 419-9180 Fax (847) 419-1515

(800) 503-9180

www.transcell.net