

TI-1620



INDICATOR

The TI-1600 Series are available in either an ABS NEMA 12 or a Stainless Steel NEMA 4X enclosure. These general purpose NTEP and Canadian approved at 10,000 division digital indicators have a full numeric keypad for ease of data input. The TI-1600 and TI-1620 are equipped with a bright 1" LED display for easy viewing. Both units are capable of displaying up to 50,000 display divisions and supply enough current to drive 8-350 Ω load cells. This Series comes standard with a full duplex RS-232, simplex RS-232C and a simplex passive 20 mA current loop serial port.



TRANSCCELL TECHNOLOGY, INC.

TI-1620


Standard Features & Benefits:

- **DIVISIONS**- NTEP and Canadian approved for 10,000 Divisions
- **DISPLAYS**- Up to 50,000 Graduations
- **SERIAL PORT**- Full Duplex RS-232 Serial Port - Simplex RS-232/20mA current loop
- **STAND**- Heavy Duty Swivel Mounting Stand
- **DISPLAY**- Large, easy to read LED
- **FULL FRONT PANEL CONFIGURATION**
- **GROSS/NET/TARE**- Print Ticket Mode with 6 digit ID number
- **TARE AND APW STORED IN NON-VOLATILE MEMORY**
- **ENCLOSURE**- Stainless Steel NEMA 4x / IP65
- **LOAD CELLS**- Drives up to eight 350 Ω Load Cells
- **INTERNAL POWER SUPPLY**
- **TIME / DATE STANDARD**
- **CUSTOM UNIT**
- **PIECE COUNTING FUNCTION**
- **CE ELECTROMAGNETIC COMPATIBILITY**
- **WATCHDOG CIRCUITRY**
- **KEYBOARD TARE ENTRY**
- **KEYBOARD ID ENTRY**

Specifications:

Load Cell Excitation: +10 VDC	Display: 1.0", 6-Digit LED, Green
Load Cell Current: Drives up to eight 350 Ω Load Cells	Operating Temperature: 14°F to 104°F (-10°C to 40°C)
Analog Signal Input Range: 0.2 mV/V min. to 3.0 mV/V max	A/D Resolution: Up to 300,000 internal counts at 3 mV/V
A/D Conversion Rate: Up to 25 meas/sec	Annunciators: Zero, Tare, Gross, Tare, lb, kg, Stable, Net, Pieces
Analog Sensitivity: 0.4 μ V/grad, Minimum 1.0 μ V/grad recommended minimum for Legal-for-Trade	Key Functions: Zero, Net/Gross, Tare, Units, Sample, APW, Dec. Pt., CL, 0-9
CE Electromagnetic Compatibility: Directive No. 89/336/EEC, EN50082-1, EN61000-4, EN55011	Serial Output: Full duplex RS-232C Simplex RS-232C Simplex 20mA Current Loop, Passive
Current Consumption: 200mA + 30mA per 350 Ω Load Cell	Power (Standard): 110/220 VAC, 50/60 Hz
Display Resolution: Up to 50,000 external grads, selectable	Power (Optional): 12 VDC
Canadian Weight & Measurements: General Class III at 10,000 division. Approval Number AM-5305	NIST Classification: H-44 Class III/IIIL at 10,000 divisions C.O.C. #99-017
Warranty: 1 year limited warranty applies	

Dimensions:



TRANSCCELL TECHNOLOGY, INC.

975 Deerfield Pkwy, Buffalo Grove, IL 60089
Tel (847) 419-9180 Fax (847) 419-1515

(800) 503-9180

www.transcell.net

Version 1.2, 4/04/08

YOUR AUTHORIZED TRANSCCELL DEALER IS:



Specifications and features subject to change without notice.