



“S” Type





Capacities

5kg, 7.5kg, 10kg, 15kg, 20kg, 30kg, 50kg, 75kg, 100kg

Features

- S-Type load cell
- Aluminum construction
- Easy to install, stable & reliable
- Suitable for tension measurement, batching systems, industrial scales and package systems, etc.

Schematic



Capacities		A	B	C	D	E	F	G	H	M
5kg~100kg	mm	64	56	28	70	21	18	9	35	M8×1.25

Specifications

Rated Output	2.0mV/V $\pm 1\%$	Safe Temp. Range	-10°C to + 70°C
Zero Balance	$\pm 3\%$ of rated output	Temp. Compensated	-10°C to + 40°C
Creep after 30 minutes	$\pm 0.03\%$ of rated output	Safe Overload	150%
Nonlinearity	$\pm 0.03\%$ of rated output	Input Impedance	410 ohm ± 5 ohm
Hysteresis	$\pm 0.03\%$ of rated output	Output Impedance	350 ohm ± 3 ohm
Repeatability	$\pm 0.03\%$ of rated output	Insulation Resistance	≥ 5000 M ohm (50V DC)
Temp. effect on output	$\leq 0.002\%$ of applied output/°C	Rated Excitation	10V DC/AC
Temp. effect on zero	$\leq 0.002\%$ of rated output/°C	Maximum Excitation	15V DC/AC
Wire Length	2.75m	Wire Material	Red(+ E) Black(- E) White(- S) Green(+ S)