

## Weighing Indicator

TI-2700  
weighing indicator



### Features

- LCD graphic display 6.1 x 3.15" (154.1 x 80mm)
- Truck in/out, 1000 ID memory
- Time and date
- Current loop for remote display
- Two RS232 serial ports
- Mini QWERTY keyboard included for fast typing
- Power up to 16, 350 ohms load cells
- Saves up to 2,000 weighings
- Works with digital or analog load cells
- Stainless Steel NEMA 4X
- Prints ticket with TM-298 or LX-350
- Menu Password

Specifications					
Hardware	Voltage range: 85~245 Vcc	Details of Road System	Storage of weighing datas		
	Consumption: 10W		ID (auto increment)		
	Operating Temperature: -10°C ~ 40°C		Time and Date		
	Protection Degree: IP-65		Vehicle Plate		
	Material: Stainless steel		Customer ID		
Interface	Graphic Display TFT 7" RGB 800x480 pixels		Product ID	Invoice	
	Frontal panel with 25 keys, including quick navigation		Lot number	Silo	
	Keyboard QWERTY (standard mini DIN PS/2 USB connector) + quick navigation keys (F1 to F12)		Applicable discounts	Driver	PH
	Serial output to printers Epson LX300			Identification document	PHM
	Serial output RS232 or RS485 (two wires) to communication with PC and other devices			Type of freight	Faulty
	Ethernet Communication (optional)	Lot number		Defective	Tax
Road operations	Allows single weighing	Digital Protocols		PHM	Technical break
	Stores up to 32768 weighing records			Faulty	Cleaning/Drying
	Base with up to 1600 clients and 1600 products pre-registered		Defective	Defective break	Brokes
	Base with up to 40 pre-registered tares, allowing manual tare		Defective break	Impurities	Humidity
	Up to 14 tips of discounts		Impurities	Impurities break	Others
	Prints weighing tickets		Transcell, HBM (C16i,AD104, AD103C), Revere (DSC and DSC2), Vishay (DHS) and KeLi		
	Various options for reports				
Up to 16 digital or analog load cells					

## Weighing Indicator

TI-2700  
weighing indicator

### Components List



Sealing screw



Cable gland in stainless steel



Lock-nut in stainless steel



Power cable



Bracket fixing knob



Battery lithium 3V 20mm



Power supply PWR08A



Washer




Nylon spacer



Screw M3 x 0,5



USB QWERTY Keyboard



TFT Display 7"



Housing in stainless steel



Main board



Panel with keypad



Flat cable



LX300 printer cable



Serial RS232 cable



QWERTY Keyboard cable

### Dimensions

